

DATA SHEET

ECOSEAL Ultra HD Clear TARMAC BINDER sealer - (ultra high solids)

DESCRIPTION

A highly durable, solvent free, clear ULTRA HIGH solids tarmac binder sealer
Waterproofs to resist the formation of moss, lichen and weed growth
Prevents penetration of dirt, oil and fuels
Protects against frost and reduces surface deterioration
Environmentally friendly
Heavy duty

USES

Ready for use as a binding/ sealer aid for old new Tarmac/ Macadam

COLOUR RANGE

Milky white in appearance, dries clear, non enhancing

PACK SIZE

20 litre

SPREADING RATE

1st coat 60-80 m² approx per 20 ltr by roller
2nd coat 80-120 m² approx per 20 ltr by roller

2 coats for best results
Surface should be structurally sound

DRYING TIME

Dry to walk on usually within 2hr - During normal temps
Lower temps and areas in the shade will extend drying time
Recoat when dry
Do not park vehicles on surface for 48 hrs

PREPARATION

All surfaces should be clean and free from loose debris, flaking material, dust, dirt, grease and vegetative growth.

APPLICATION

Cut in edges with a large fence brush
Course droplet low level spray, broom, brush or roller
*Avoid over flooding surface
* Brush out pooled sealer
Do not leave pooled sealer to cure

CLEANING

For cleaning equipment use water

PRECAUTIONS

NON FLAMMABLE

Do not use below 8 °C. Protect stored product from frost and freezing
For your protection and safety, wear gloves, overalls, and eye protection
Keep children and animals away from sealed surface till dry
Be aware that sealed tarmac will repel surface water
Do not allow sealer to pool - Do not seal wet or damp tarmac

Do not start sealing if rain is imminent
Do not eat, drink, or smoke when using

Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with ECOSEAL Ultra HD clear TARMAc BINDER sealer

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from the skin with soap and water

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request