

DATA SHEET

PREMIUM Ultra Block paving sealer - (High solids)

DESCRIPTION

The latest high quality acrylic co-polymer resin, suspended in our unique blend of organic solvents

Designed to protect block paved areas by repelling water, dirt, oil and fuels

Inhibits weed and moss growth

Bonds jointing sand solid

USE

Ready to use for sealing porous cement block paving

COLOUR RANGE

Clear, enhances colour, restores colour

PACK SIZE

20 litre

SURFACE FINISH

1 or 2 coat application

Matt (slight sheen) 1 coat

Glossier effect 2 coats

SPREADING RATE

60-70 sq mtr approx per 20 ltr drum when spraying block paving

100 – 140 sq mtr approx per 20 ltr on 2nd coat

More when brushing or rolling

DRYING TIME

Dry to walk on usually within 2hr - During normal temps

Lower temps will extend drying time

Recoat when dry enough to walk on (1-2hr)

Do not park vehicles on surface for 48 hrs

PREPARATION

Apply above 5°C. Do not apply to wet/ damp surfaces, if rain is imminent or if efflorescence is present.

New blocks

Apply as soon as possible after installation. Ensure surface is clean, dry and remove excess sand.

Old blocks

Fully clean off surfaces with power wash, apply Premium weed and moss inhibitor. Allow to dry thoroughly and re-apply jointing sand prior to sealer application.

APPLICATION

By course droplet low level spray, brush or roller. Avoid excess pooling and over coating.

CLEANING

For cleaning equipment use Premium SD Thinners. (Not White Spirit)

PRECAUTIONS

Flammable. Keep away from sources of ignition

High VOC - Do not breathe vapour or spray

Do not eat, drink, or smoke when using

Ensure good ventilation during application

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with a recognized hand cleaner

Keep out of reach of children

Do not use near fishponds

Toxic to aquatic organisms

May cause long term adverse effects in the aquatic environments

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request