

DATA SHEET

PREMIUM Ultra Imprinted concrete sealer - (High solids)

DESCRIPTION

The latest high quality acrylic co-polymer resin, suspended in our unique blend of organic solvents

Designed to protect Imprinted concrete areas by repelling water, dirt, oil and fuels
Protects against frost and reduces surface deterioration

USE

Ready to use for sealing Imprinted Concrete

COLOUR RANGE

Clear, enhances colour, restores colour

PACK SIZE

20 litre

SURFACE FINISH

1 or 2 coat application

Matt (slight sheen) 1 coat

Glossier effect 2 coats

SPREADING RATE

80-100 m² per 20 ltr when spraying, more when brushing or rolling

120-160 m² per 20 ltr 2nd coat when spraying, more when brushing or rolling

DRYING TIME

Dry to walk on usually within 2hr - During normal temps

Lower temps will extend drying time

Recoat when dry enough to walk on (1-2hr)

Do not park vehicles on surface for 48 hrs

PREPARATION

Ensure surface is clean and dry. Apply above 5°C. Do not apply to wet/ damp surfaces, if rain is imminent

APPLICATION

By course droplet low level spray, brush or roller. Avoid excess pooling and over coating.

CLEANING

For cleaning equipment use Premium SD Thinners. (Not White Spirit)

PRECAUTIONS

Flammable. Keep away from sources of ignition

High VOC - Do not breathe vapour or spray

Do not eat, drink, or smoke when using

Ensure good ventilation during application

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with a recognized hand cleaner

Keep out of reach of children

Do not use near fishponds

Toxic to aquatic organisms

May cause long term adverse effects in the aquatic environments

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request